


# EX-H-POT

●마크의 설명은 P2를 보십시오.



단위 : mm

공구 NO EDP NO.	규격 Thread Size	정도 TAP Limit	식부 Lcf	전장 L	나사길이 Lc	목부길이 L1	생크경 d	홈수 Flutes
16696K	M1.2 X 0.25	OH1	5P	32	8	-	3	2
16698K	M1.4 X 0.3	OH1	5P	34	9	-	3	2
16700K	M1.7 X 0.35	OH1	5P	36	11	-	3	2
16702K	M2 X 0.4	OH1	5P	40	12	-	3	2
16704K	M2.3 X 0.4	OH1	5P	42	13	-	3	2
16706K	M2.5 X 0.45	OH2	5P	44	14	-	3	2
16708K	M2.6 X 0.45	OH2	5P	44	14	-	3	2
215368K	M3 X 0.5	OH2	5P	46	11	19	4	3
216065K	M3 X 0.6	OH2	5P	46	11	19	4	3
216074K	M3.5 X 0.6	OH2	5P	48	13	20	4	3
216089K	M4 X 0.5	OH2	5P	52	13	21	5	3
215386K	M4 X 0.7	OH2	5P	52	13	21	5	3
216083K	M4 X 0.75	OH2	5P	52	13	21	5	3
216092K	M4.5 X 0.75	OH2	5P	55	13	21	5	3
216105K	M5 X 0.5	OH2	5P	60	16	24	5.5	3
216103K	M5 X 0.75	OH2	5P	60	16	24	5.5	3
215401K	M5 X 0.8	OH2	5P	60	16	24	5.5	3
216098K	M5 X 0.9	OH2	5P	60	16	24	5.5	3
216110K	M5.5 X 0.5	OH2	5P	60	17	25	5.5	3
216108K	M5.5 X 0.9	OH2	5P	60	17	25	5.5	3
216120K	M6 X 0.5	OH2	5P	62	19	29	6	3
216116K	M6 X 0.75	OH2	5P	62	19	29	6	3
215413K	M6 X 1	OH2	5P	62	19	29	6	3
216129K	M7 X 0.5	OH2	5P	65	19	33	6.2	3
216127K	M7 X 0.75	OH2	5P	65	19	33	6.2	3
216122K	M7 X 1	OH2	5P	65	19	33	6.2	3
216141K	M8 X 0.5	OH2	5P	70	22	37	6.2	3
216137K	M8 X 0.75	OH2	5P	70	22	37	6.2	3
216134K	M8 X 1	OH2	5P	70	22	37	6.2	3
215431K	M8 X 1.25	OH3	5P	70	22	37	6.2	3
216148K	M9 X 1	OH2	5P	72	22	38	7	3
216144K	M9 X 1.25	OH3	5P	72	22	38	7	3
216167K	M10 X 0.5	OH2	5P	75	24	41	7	3
216165K	M10 X 0.75	OH2	5P	75	24	41	7	3
216163K	M10 X 1	OH3	5P	75	24	41	7	3
215460K	M10 X 1.25	OH3	5P	75	24	41	7	3
215456K	M10 X 1.5	OH3	5P	75	24	41	7	3
216176K	M11 X 0.75	OH2	5P	80	25	48	8	3
216174K	M11 X 1	OH3	5P	80	25	48	8	3
216172K	M11 X 1.25	OH3	5P	80	25	48	8	3
216169K	M11 X 1.5	OH3	5P	80	25	48	8	3
216194K	M12 X 0.5	OH2	5P	82	29	48	8.5	3
216193K	M12 X 0.75	OH2	5P	82	29	48	8.5	3
216191K	M12 X 1	OH3	5P	82	29	48	8.5	3
215487K	M12 X 1.25	OH3	5P	82	29	48	8.5	3
215483K	M12 X 1.5	OH3	5P	82	29	48	8.5	3
215480K	M12 X 1.75	OH4	5P	82	29	48	8.5	3

■ 생크 사각부치수 Lk, K는 T-209페이지를 참조하십시오.

1. 정도란  은 2급 암나사 상당 적용 탭 추천 정도입니다.(T-192페이지참조)
2. M9이하의 돌출센터로 되어 있습니다.

공구 NO EDP NO.	규격 Thread Size	정도 TAP Limit	식부 Lcf	전장 L	나사길이 Lc	목부길이 L1	생크경 d	홈수 Flutes
216203K	M13 X 1	OH2	5P	88	30	48	9.5	3
216199K	M13 X 1.5	OH3	5P	88	30	48	9.5	3
216195K	M13 X 1.75	OH3	5P	88	30	48	9.5	3
216220K	M14 X 1	OH3	5P	88	30	48	9.5	3
216216K	M14 X 1.25	OH3	5P	88	30	48	9.5	3
215512K	M14 X 1.5	OH3	5P	88	30	48	9.5	3
215509K	M14 X 2	OH4	5P	88	30	48	9.5	3
216268K	M16 X 1	OH3	5P	95	32	52	12.5	3
215560K	M16 X 1.5	OH3	5P	95	32	52	12.5	3
215557K	M16 X 2	OH4	5P	95	32	52	12.5	3
216282K	M17 X 1	OH3	5P	100	37	55	13	3
216286K	M17 X 1.5	OH3	5P	100	37	55	13	3
216304K	M18 X 1	OH3	5P	100	37	55	14	3
215601K	M18 X 1.5	OH4	5P	100	37	55	14	3
216297K	M18 X 2	OH4	5P	100	37	55	14	3
215593K	M18 X 2.5	OH4	5P	100	37	55	14	3
216341K	M20 X 1	OH3	5P	105	37	58	15	3
215637K	M20 X 1.5	OH4	5P	105	37	58	15	3
216333K	M20 X 2	OH4	5P	105	37	58	15	3
215629K	M20 X 2.5	OH4	5P	105	37	58	15	3
216358K	M22 X 1	OH2	5P	115	38	63	17	3
215653K	M22 X 1.5	OH4	5P	115	38	63	17	3
216349K	M22 X 2	OH4	5P	115	38	63	17	3
215645K	M22 X 2.5	OH4	5P	115	38	63	17	3
216385K	M24 X 1	OH2	5P	120	45	66	19	3
215681K	M24 X 1.5	OH4	5P	120	45	66	19	3
216377K	M24 X 2	OH4	5P	120	45	66	19	3
215673K	M24 X 3	OH4	5P	120	45	66	19	3
216397K	M25 X 1.5	OH4	5P	130	45	71	19	3
216389K	M25 X 3	OH4	5P	130	45	71	19	3
216409K	M26 X 1.5	OH4	5P	130	45	71	20	3
216407K	M26 X 2	OH3	5P	130	45	71	20	3
216405K	M26 X 3	OH4	5P	130	45	71	20	3
216428K	M27 X 1	OH2	5P	130	45	71	20	3
216425K	M27 X 1.5	OH4	5P	130	45	71	20	3
216421K	M27 X 2	OH4	5P	130	45	71	20	3
216417K	M27 X 3	OH4	5P	130	45	71	20	3
315326k	M28 X 1	OH2	5P	135	48	74	21	3
216441K	M28 X 1.5	OH4	5P	135	48	74	21	3
216437K	M28 X 2	OH4	5P	135	48	74	21	3
216434K	M28 X 3	OH4	5P	135	48	74	21	3
216465K	M30 X 1	OH2	5P	135	48	74	23	3
216461K	M30 X 1.5	OH4	5P	135	48	74	23	3
216457K	M30 X 2	OH4	5P	135	48	74	23	3
216453K	M30 X 3	OH4	5P	135	48	74	23	3
216450K	M30 X 3.5	OH5	5P	135	48	74	23	3

